

## Nylon & Polyester Double Braid

This double braided rope is constructed with a 100% polyester cover and a 100% nylon core. It is available with urethane coating for color coding and to maximize abrasion resistance and minimize water absorption.

### Features

- Specific gravity of 1.24
- High energy absorption
- Extremely high strength
- Good dielectric properties
- Urethane coated cover available
- Spliceable
- Exceeds the requirements of CSA 2.98-2007 standard

### Applications

- Rigging lines
- Pulling lines
- Lift lines
- Ski lift evacuation rope



## SPECIFICATIONS

- Standard colours: Orange, White
- Other colours and diameters available upon request

| Code   | Diameter |       | kg per 100m | lbs per 100ft | Avg. Strength |         |
|--------|----------|-------|-------------|---------------|---------------|---------|
|        | (mm)     | (in)  |             |               | (kg)          | (lbs)   |
| DBPN08 | 6,4      | 1/4   | 3,0         | 2,0           | 1 135         | 2 500   |
| DBPN10 | 7,9      | 5/16  | 4,5         | 3,0           | 1 725         | 3 800   |
| DBPN12 | 9,5      | 3/8   | 6,0         | 4,0           | 2 270         | 5 000   |
| DBPN14 | 11,1     | 7/16  | 8,3         | 5,6           | 3 405         | 7 500   |
| DBPN16 | 12,7     | 1/2   | 11,2        | 7,5           | 5 448         | 12 000  |
| DBPN20 | 15,9     | 5/8   | 19,2        | 12,9          | 7 718         | 17 000  |
| DBPN24 | 19,1     | 3/4   | 25,3        | 17,0          | 10 125        | 22 500  |
| DBPN32 | 25,4     | 1     | 46,2        | 31,0          | 19 068        | 42 000  |
| DBPN40 | 31,8     | 1-1/4 | 68,5        | 46,0          | 29 510        | 65 000  |
| DBPN48 | 38,1     | 1-1/2 | 98,3        | 66,0          | 40 860        | 90 000  |
| DBPN64 | 50,8     | 2     | 172,8       | 110,0         | 64 922        | 143 000 |

### Barry Cordage Ltd.

6110 boul. des Grandes Prairies  
 Montreal QC H1P 1A2 Canada  
 ☎ 514.328.3888 📠 514.328.1963  
 1.800.305.2673 (Canada / USA)