

LV401 Diving Lifeline



Designed for commercial/professional divers, this lifeline is used as an umbilical and/or 2nd (back-up) lifeline when used with the Barry Sub Divo Lite and Pro diving harnesses.

Available with a protective Cordura jacket to integrate communication or electric cable.

Meets and exceeds CSA standard Z275-2-04 and Quebec RSST requirements for diving lifelines.



Optional Quick-Zip protective jacket



Heavy Duty stainless steel thimble



Double action Wichard stainless steel carabiner

SPECIFICATIONS

- 12-strand Dyneema® (HMPE) rope , 13 mm (½") diameter
- Polyurethane coated for abrasion and U.V. resistance
- Available with 2 end options:
 - HD stainless steel thimble
 - Double action Wichard stainless steel large carabiner
- Splice with lock-stitch and lashing
- The whole assembly is pre-stretched at 900 kg (2 000 lbs) to remove mechanical elongation
- Elastic elongation : less than 1% at 30% of break strength
- Minimum break strength: 13 900 kg (30 600 lbs)
(2 800 kg (6 000 lbs) with Wichard carabiner)
- Weight: 9.5 kg/100 m (6.4 lbs/100 ft)
- Comes with transport and storage bag
- Length as requested

Barry Cordage Ltd.

6110 boul. des Grandes Prairies
Montreal QC H1P 1A2 Canada
☎ 514.328.3888 ☎ 514.328.1963
1.800.305.2673 (Canada / USA)