

Oletec-12[®]

Oletec-12[®] is a hollow braided 12-strand rope using 100% polyolefin high tenacity co-polymer fiber. It is designed with single or two ply construction depending upon nominal size. Oletec-12[®] is designed for commercial and marine applications where an easily handled, high strength, floating rope is required.

Features

- Specific gravity of 0.99
- Non-Rotating and torque-free
- Lightweight
- UV Stabilized
- No water absorption
- Good abrasion resistance
- Mildew-resistant
- Easy to splice

Applications

- Pulling lines
- Electric utilities

Dielectric properties

- Passed the ASTM F1701-05 standard for dry and wet conditions



SPECIFICATIONS

- Standard colour: Green

Diameter		kg per 100m	lbs per 100ft	Average Strength	
(mm)	(in)			(kg)	(lbs)
6,4	1/4	1,6	1,1	681	1 500
9,5	3/8	4,0	2,7	1 589	3 500
12,7	1/2	7,3	4,9	2 724	6 000
15,9	5/8	13,0	8,7	4 495	9 900
19,1	3/4	16,2	10,9	5 448	12 000
25,4	1	30,5	20,5	9 534	21 000
31,8	1-1/4	40,8	27,4	12 939	28 500
38,1	1-1/2	59,6	40	18 160	40 000
44,5	1-3/4	87,9	59	26 992	58 000
50,8	2	107,2	72	31 326	69 000

Barry Cordage Ltd.

6110 boul. des Grandes Prairies
 Montreal QC H1P 1A2 Canada
 ☎ 514.328.3888 📠 514.328.1963
 1.800.305.2673 (Canada / USA)