

## Static Rope<sup>†</sup>

Flexible kernmantle construction with braided polyester cover and nylon core. Static rope is designed to meet or exceed NFPA 1983 standard for rescue ropes.

### Features

- Meets or exceeds NFPA 1983 standards
- Good shock mitigation
- Maintains firm round shape
- Not spliceable

### Applications

- Theatrical rigging
- High angle rescue



### Barry Cordage Ltd.

6110 boul. des Grandes Prairies  
 Montreal QC H1P 1A2 Canada  
 ☎ 514.328.3888 📠 514.328.1963  
 1.800.305.2673 (Canada / USA)

## SPECIFICATIONS

- Standard colour: Black
- Other colours available upon request

Diameter (mm)	(in)	kg per 100m	lbs per 100ft	Avg. Strength		Min. Strength	
				(kg)	(lbs)	(kg)	(lbs)
9,5	3/8	3,0	2,0	2 600	5 700	2 200	4 800
11,0	7/16	8,9	6,0	3 700	8 200	3 200	7 000
13,0	1/2	11,9	8,0	5 000	11 000	4 200	9 400
15,5	5/8	16,7	11,2	6 100	13 500	5 200	11 500

<sup>†</sup>Static Rope is a trademark of Samson Rope Technologies