

THE

GUARDDOG

SELF-CLOSING SAFETY GATE



The GuardDog Self Closing Gate from BlueWater is tough, durable and easy to install. Use it on ladders or in plant guardrail barriers.

The gate arm is dimensioned to match top and mid-rail heights of OSHA compliant guardrails. When the gate is installed with the top rail at OSHA's recommended nominal guardrail height of 42" above the work surface, the bottom rail of the gate is at OSHA's nominal mid-rail height of 21".

Installation is fast!! Our gate comes fully assembled and includes securing hardware for pipe/tubing installation. It requires only one 1/2" wrench and 5 minutes to install.

The gates come in 5 nominal sizes ranging from 18" to 48". Each gate size can be laterally adjusted up to 6" (-3" to +3") to ensure the gate fits properly in your opening for maximum safety.

The GuardDog Safety Gate comes in three finishes: Powder Coat Safety Yellow, Hot-Dip Galvanized or 316 Stainless Steel. Special colors are available upon request (min. paint charges may apply).



KEY FEATURES

- ▶ Gate arm is dimensioned to provide maximum opening coverage. The rails are spaced to match OSHA guardrail regulations.
- ▶ Our Universal Hinge Assembly fits various railing types up to 2" O.D. or flat surface mounting. Adapter kits are available for larger or uniquely shaped railings.
- ▶ Each gate is capable of swinging in either direction - simply invert the installation position.
- ▶ The self-closing feature employs two stainless steel torsion springs.
- ▶ 5 nominal sizes are available, and each is adjustable laterally up to 6".
- ▶ Gates are available in powder coat safety yellow, hot-dip galvanized, or stainless steel.



- ▶ Gate Hoop Compression Clamp ensures quick set-up and makes adjustability a 'snap'.



A COMPANY OF INNOVATION - NOT IMITATION

4064 Peavey Rd., Chaska, MN 55318 • Toll Free: 866-933-2935
info@bluewater-mfg.com • www.bluewater-mfg.com