

Barry D.E.W. Line® Insulating Safety Net

Product code : **CN-NK1000C-70100-2.5**

DESCRIPTION

This insulating safety net, assembled using our proprietary Barry D.E.W. Line® rope and our specially designed clips, has excellent dielectric properties and is designed to serve as a safety barrier or guard structure which is installed on rider poles or infrastructures for power lines, roads, and railway crossings. It protects and secures apparatus while performing live work under AC or DC condition.

Meets or exceeds the dry or wet electrical requirements of


- IEC 62192:2009
- ASTM F1701-12

Arc-Flash rated

- Resistant to 40 cal/cm^2 (category 4)

Features

- Unique insulating properties
- Cleanable and easy to maintain and test
- Exceptionally low leakage current, whether dry or wet
- Protection from high fault current
- High strength
- Low elongation
- Lightweight and low volume
- Fully sealed and hydrophobic
- Smooth surface
- High abrasion resistance
- Easy to deploy
- Excellent resistance to UV



TECHNICAL SPECIFICATIONS

Rope Diameter	1/4" (6 mm)
Mesh Size	2'-6" x 2'-6" (0.75 m x 0.75 m)
Mesh break strength	600 lb (272 kg) each
Thimble to thimble break strength	2 000 lb (907 kg)
Terminations	Stainless steel thimble every 5' (1.5 m) on 2 sides
Colour	Black rope with orange junction clips
Weight	185 lb (84 kg) for 70' x 100' (21 m x 30.5 m) net
Standard dimensions	70' x 100' (21 m x 30.5 m); 70' x 150' (21 m x 45.7 m); 70' x 200' (21 m x 61 m)

Note: Available in other widths, lengths, mesh sizes.

PRODUCT PAGE AND REFERENCES

This sheet reflects the data published on the product page on the generation date.

For the current version, scan the code or visit:

<https://www.barry.ca/products/cn-nk1000c-barry-d-e-w-line-insulating-safety-net>

User instructions manual : <https://www.barry.ca/pages/instructions-manual-barry-d-e-w-line-insulating-rope-equipment>



Product page



User manual