
Barry D.E.W. Line® R4 Tower and Bucket Rescue Kit

Product code : **ENS-R4-HLNF-065**

DESCRIPTION









The Barry D.E.W. Line® Tower and Bucket Rescue Kit is a compact self-contained and easily deployed system designed for self-evacuation from energized work positions.

The Rescue Kit for bucket trucks and tower self-evacuation includes the Barry D.E.W. Lines dielectric rescue rope, renowned for its exceptional performance and reliability. The rope is securely stored in a hermetically sealed bag, ensuring easy inspection and preserving its dielectric properties. Designed for quick installation, deployment, and use in critical situations, this kit is ideal for the self-rescue of operators working in energized zones. The standard rope provided offers superior insulating properties, consistent with the Barry D.E.W. Lines range. Additionally, we offer rope options with specialized features, such as inherent fire resistance, to cater to specific operational requirements.

Like all Barry D.E.W. Lines ropes, this kit is easy to inspect and recondition as needed. We also offer technical support and training to ensure proper use and maintenance.

The kit includes a Rescue 8 descender, highly efficient for this application. Alternative descender options are also available to accommodate your specific needs and standard operating procedures (SOPs).

Meets or exceeds the dry or wet electrical requirements of

- IEC 62192-2009
- ASTM F1701-12

Arc-Flash rated

- Resistant to 40 cal/cm^2 (category 4)

Flammability Rating

- Conforms to 14 CFR 25.853 Appendix F

Fire Resistance

- Optional inherently fire resistant (IFR) to NFPA 701 is available on request

Features

- Pre-assembled kit
- Uses Barry D.E.W. Line® Rescue rope

Barry has a policy of continuous improvement and reserves the right to update product or components without prior notice. This sheet reflects the data published on barry.ca on the generation date. Terms of service : https://www.barry.ca/policies/terms-of-service

- Comes with transport bag

Applications

- Bucket trucks and tower self-evacuation

TECHNICAL SPECIFICATIONS

Rated Load	min. 115 lb (52 kg) max. 350 lb (150 kg)
Standard Lengths	65’ (20 m) reach

Note: Available in other lengths. Contact Barry for more information.

Kit includes

- Barry D.E.W. Line® NF3400 Dielectric Rescue Rope
- 2 x Steel carabiners
- 2 x 6’ (1.8 m) anchor strap
- 1 x Figure 8 rescue descender
- Transport bag

PRODUCT PAGE AND REFERENCES

This sheet reflects the data published on the product page on the generation date. For the current version, scan the code or visit: https://www.barry.ca/products/ens-r4-hlnf-065-barry-d-e-w-line-r4-tower-and-bucket-rescue-kit

User instructions manual : https://www.barry.ca/pages/instructions-manual-barry-d-e-w-line-insulating-rope-equipment

Product page

User manual

Barry has a policy of continuous improvement and reserves the right to update product or components without prior notice. This sheet reflects the data published on barry.ca on the generation date. Terms of service : https://www.barry.ca/policies/terms-of-service