

Barry D.E.W. Line® Insulating Throw Line

Product code : **HL-NA50-300**

DESCRIPTION

This insulating lightweight and tangle free throw line was developed for use with most rope and line launchers. It features excellent dielectric properties and is designed for direct contact with AC or DC energized conductors and structures.

Meets or exceeds the dry and wet electrical requirements of


- IEC 62192:2009
- ASTM F1701-12

Features

- Unique insulating properties
- Cleanable with smooth surface
- Knottable and easily attaches to throw weight pouches
- Exceptionally low leakage current, whether dry or wet
- Protection from high fault current
- Lightweight, flexible, and low volume
- Hydrophobic
- High abrasion resistance
- Easy to deploy and flies well
- Excellent resistance to UV
- Comes with transport bag and storage reel
- Optional barry D.E.W. Line® Stand-Up bag available to facilitate throws

Applications

- Live line work
- Arborists



TECHNICAL SPECIFICATIONS

Working Load Limit	30 lb (13.6 kg)
Diameter	1/8" (3 mm)
Colour	Black
Weight	0.7 lb (0.3 kg) / 100 ft (30.5 m)
Standard Lengths	300' (91 m) and 500' (152 m)

Note: Available in other lengths, diameters and working load limits. Contact Barry for more information.

PRODUCT PAGE AND REFERENCES

This sheet reflects the data published on the product page on the generation date.

For the current version, scan the code or visit:

<https://www.barry.ca/products/hl-na50-barry-d-e-w-line-insulating-throw-line>

User instructions manual : <https://www.barry.ca/pages/instructions-manual-barry-d-e-w-line-insulating-rope-equipment>



Product page



User manual