

Barry D.E.W. Line® Insulating Tag Line

Product code : **HL-NK1000-2S-010**

DESCRIPTION

Insulating rope tool offering excellent dielectric properties and designed for performing live work on AC or DC energized apparatus.

Meets or exceeds the dry or wet electrical requirements of

- IEC 62192:2009
- ASTM F1701-12

Arc-Flash rated

- Resistant to 40 cal/cm^2 (category 4)

Features

- Unique insulating properties
- Cleanable and easy to maintain and test
- Exceptionally low leakage current, whether dry or wet
- Protection from high fault current
- High strength
- Low elongation
- Lightweight and low volume
- Fully sealed and hydrophobic
- Smooth surface
- High abrasion resistance
- Easy to deploy
- Excellent resistance to UV
- High visibility sealed termination at each end
- Comes with transport bag



TECHNICAL SPECIFICATIONS

Working Load Limit	200 lb (90 kg)
Diameter	1/4" (6 mm)
Terminations	Stainless steel thimble at each end
Colour	Black with bright orange terminations
Weight	0.78 lb (0.35 kg) for 20' length
Standard Lengths	20' (6.1 m), 30' (9.1 m), 40' (12.2 m)

Note: Available in other lengths. Contact Barry for more information.

PRODUCT PAGE AND REFERENCES

This sheet reflects the data published on the product page on the generation date.

For the current version, scan the code or visit:

<https://www.barry.ca/products/hl-nk1000-barry-d-e-w-line-insulating-tag-line>

User instructions manual : <https://www.barry.ca/pages/instructions-manual-barry-d-e-w-line-insulating-rope-equipment>



Product page



User manual