

Barry D.E.W. Line® Insulating Work Rope

Product code : **HL-NP2800-010**

Meets or exceeds the dry or wet electrical requirements of

- IEC 62192:2009
- ASTM F1701-12

Arc-Flash rated

- Resistant to 40 cal/cm² (category 4)

Features

- Unique insulating properties
- Knottable
- Cleanable and easy to maintain and test
- Exceptionally low leakage current, whether dry or wet
- Protection from high fault current
- High strength
- Low elongation
- Light weight and low volume
- Fully sealed and hydrophobic
- Smooth surface
- High abrasion resistance
- Easy to deploy
- Excellent resistance to UV
- Sealed termination with stainless steel thimble at each end
- Comes with transport bag



TECHNICAL SPECIFICATIONS

Minimum Break Strength*	6 300 lb (2 857 kg)
Working Load Limit	1 260 lb (571 kg)
Diameter	1/2" (13 mm)
Colour	Orange
Standard Lengths	50' (15.2 m), 100' (30.5 m), 150' (45.7 m)

Note: Available in other lengths. Contact Barry for more information.

*Reduce break strength by 50% when using knots.

PRODUCT PAGE AND REFERENCES

This sheet reflects the data published on the product page on the generation date.

For the current version, scan the code or visit:

<https://www.barry.ca/products/hl-np2800-barry-d-e-w-line-insulating-work-rope>

User instructions manual : <https://www.barry.ca/pages/instructions-manual-barry-d-e-w-line-insulating-rope-equipment>



Product page



User manual