

TECHNICAL DATA SHEET

1091550

Lifting Beam for Transformer

Lifting Beam designed for lifting electricity distribution transformers, or for other loads requiring a two point lifting system.

The Lifting Beam is made of nylon material, while the rope is made of low elongation Dyneema® fiber. Height adjustment is made with the adjustable splices.

Features:

- Reinforced top attachment rope
- Adjustable legs with chafe guards



Barry Cordage Ltd.

6110 boul. des Grandes Prairies Montreal QC H1P 1A2 Canada 6 514.328.3888 514.328.1963 1.800.305.2673 (Canada / USA)

www.barry.ca

Copyright © 2020 Barry Cordage Ltd.
Barry has a policy of continuous improvement and reserves the right to update product or components without prior notice.
UNCONTROLLED IF PRINTED



SPECIFICATIONS

- Bar Material: MOS2 Nylon
- Rope Material: 10 mm (3/8") Dyneema® fiber
- **Height:** Adjustable from 41 cm (16") to 58 cm (23")
- Width Between Adjustable Legs: 62 cm (24.5")
- Working Load Limit: 728 kg (1 605 lb)
- Minimum Breaking Strength: 5 100 kg (11 243 lb)
- **Weight:** 2.25 kg (5 lb)

Dyneema® is a trademark of DSM. Use of this trademark is prohibited unless strictly authorized.