

## # BSLR Helicopter Short Line

Barry short lines act as a lightweight and easy-handling intermediary between the helicopter cargo-hook and the load, when the use of a longline is not required or possible.

### System Includes

- Synthetic rope line (Dyneema® fiber)
- Master link at top end
- Permanent ID tag
- Certificate of compliance (COC)
- User instructions manual
- Transport/storage bag

### Optional / Accessories

- Protective zipper jacket (recommended)
- Non-electric swivel hook at bottom end
- Custom hardware

### Technical

- 10-year service and shelf life
- Proof-loaded to 1.5 x WLL
- Supported by Airworthiness Analysis to FAA CFR Title 14, Parts 27 & 29
- EC Machinery Directive 2006/42/EC compliant



Optional: Protective zipper jacket



Available with or without self-locking swivel hook



Master link in top thimble

## SPECIFICATIONS

Product Code (without Hook)	Product Code (with Hook)	Diameter	Working Load Limit
BSLR-3000	BSLRH-3000	7/16" (11 mm)	3 000 lb (1 361 kg)
BSLR-4500	BSLRH-4500	1/2" (13mm)	4 500 lb (2 041 kg)
BSLR-6400	BSLRH-6400	5/8" (16 mm)	6 400 lb (2 903 kg)
BSLR-8300	BSLRH-8300	3/4" (19 mm)	8 300 lb (3 764 kg)

Standard lengths: 6', 8', 10', 12', 16' and 20'  
(Other lengths available upon request)

Max. shelf life	Max. service life	Max. combined life (shelf + service)
10 years	10 years	10 years

Important: Parts are considered on-condition throughout their shelf & service life and must pass inspections and maintenance recommendations as per the manufacturer's user instructions manual.

Dyneema® is a trademark of DSM. Use of this trademark is prohibited unless strictly authorized.

[www.barry.ca](http://www.barry.ca)