

### Barry D.E.W. Line™ Dielectric Rescue Rope

High angle rescue rope for evacuation of workers in energized fields on high voltage systems (AC or DC).

Meets or exceeds the dry or wet electrical requirements of:

- IEC 62192:2009

**Arc-Flash rated**

- Resistant to 40 cal/cm<sup>2</sup> (category 4)

**Features**

- Unique insulating properties
- Exceptionally low leakage current, whether dry or wet
- Stable leakage current throughout the electrical test period
- High strength
- Low elongation
- Light weight and low volume
- Excellent resistance to changing weather conditions, UV, corona effect and temperature extremes
- Sealed sewn termination with plastic thimble at each end
- Easy storage in optional transport bag with desiccant

**Application**

- May be used with various types of descenders
- May be part of a complete rescue system which can be fully retrieved after descent



**Barry Cordage Ltd.**

6110 boul. des Grandes Prairies  
Montreal QC H1P 1A2 Canada  
☎ 514.328.3888 📠 514.328.1963  
1.800.305.2673 (Canada / USA)

[www.barry.ca](http://www.barry.ca)

Copyright © 2020 Barry Cordage Ltd.  
Barry has a policy of continuous improvement and reserves the right to update product or components without prior notice.  
UNCONTROLLED IF PRINTED



## SPECIFICATIONS

- **Minimum Break Strength\***: 3 401 kg (7 500 lb)
- **Core**: 11 mm (7/16") Technical Use Life Safety Rope
- **Outside Diameter**: 12 mm (15/32")
- **Colour**: Orange with tracer
- **Length**: Upon request

\* Reduce break strength by 50% when using knots. Use an appropriate safety factor (SF) to determine correct working load limit (WLL) for intended use.

Barry D.E.W. Line™ and all Barry D.E.W. Line™ products are trademarks of Barry Cordage Ltd. Use of these trademarks is strictly prohibited unless authorized by Barry.