

Insulating hot rope tool offering excellent dielectric properties and designed for work in energized fields on high voltage systems (AC or DC).

Assembled using our proprietary dielectric rope, it allows easy inspection and has high visibility terminations for safety.

Meets or exceeds the dry or wet electrical requirements of :

- IEC 62192:2009

Arc-Flash rated

- Resistant to 40 cal/cm² (category 4)

Features

- Unique insulating properties
- Exceptionally low leakage current, whether dry or wet
- Stable leakage current throughout the electrical test period
- High strength
- Low elongation
- Light weight and low volume
- Excellent resistance to changing weather conditions, UV, corona effect and temperature extremes
- Easy storage in provided transport bag with desiccant



Transport bag included

Barry Cordage Ltd.

6110 boul. des Grandes Prairies
Montreal QC H1P 1A2 Canada
☎ 514.328.3888 📠 514.328.1963
1.800.305.2673 (Canada / USA)

www.barry.ca



SPECIFICATIONS

- **Working Load Limit:** 90 kg (200 lb)
- **Diameter:** 6 mm (1/4")
- **Terminations:** Stainless steel thimble at each end
- **Colour:** Black with bright orange terminations
- **Weight:** 0.35 kg (0.78 lb) for 20' length
- **Standard Lengths:** 6.1 m (20'), 9.1 m (30'), 12.2 m (40')

Note: Available in other lengths, diameters and working load limits. Contact Barry for more information.