

This 100% polyester rope has a hollow braided 12-strand construction. It is designed with a single or two-ply construction depending upon nominal size. Available with a urethane coating that offers color coding options and additional abrasion resistance.

Features

- Non-rotating
- Torque free
- Very flexible and easy to handle
- Easily spliced and inspected
- Urethane coating available for abrasion resistance and color coding

Applications

- Floating dock moorings
- Pulling lines
- Lifting slings
- Tow lines
- Dock lines



SPECIFICATIONS

- Standard color: White, red, black
(Other colors available on request)

Code	Diameter		kg per 100m	lbs per 100 ft	Average Strength	
	(mm)	(in)			(kg)	(lbs)
POLY12 - 1/4	6.4	1/4	3.1	2.1	1 225	2 700
POLY12 - 5/16	7.9	5/16	4.8	3.2	1 769	3 900
POLY12 - 3/8	9.5	3/8	6.1	4.1	2 902	6 400
POLY12 - 7/16	11.1	7/16	9.4	6.3	3 628	8 000
POLY12 - 1/2	12.7	1/2	12.7	8.5	5 533	12 200
POLY12 - 5/8	15.9	5/8	19.5	13.1	9 616	21 200
POLY12 - 3/4	19.1	3/4	25.6	17.2	11 521	25 400
POLY12 - 7/8	22.2	7/8	38.4	25.8	17 055	37 600
POLY12 - 1	25.4	1	51.4	34.5	22 679	50 000
POLY12 - 1 1/8	28.6	1-1/8	61.4	41.2	29 982	66 100
POLY12 - 1 1/4	31.8	1-1/4	68.5	46.0	33 293	73 400
POLY12 - 1 1/2	38.1	1-1/2	106.2	71.3	39 825	87 800

Barry Cordage Ltd.

6110 boul. des Grandes Prairies
Montreal QC H1P 1A2 Canada
☎ 514.328.3888 📠 514.328.1963
1.800.305.2673 (Canada / USA)