

This multi-purpose Kevlar® strap was designed for positioning while working at heights (when used in conjunction with a compliant fall protection system) or for carrying and manipulating work equipment.

Thanks to the Kevlar® webbing and thread construction, it is resistant to flames and heat, and as such is a great addition to the standard equipment of firefighters or other workers that may be exposed to environments where high heat is a factor.



Barry Cordage Ltd.

6110 boul. des Grandes Prairies
 Montreal QC H1P 1A2 Canada
 ☎ 514.328.3888 📠 514.328.1963
 1.800.305.2673 (Canada / USA)

www.barry.ca

Copyright © 2024 Barry Cordage Ltd.
 Barry has a policy of continuous improvement and reserves the right to update product or components without prior notice.
 UNCONTROLLED IF PRINTED

SPECIFICATIONS

- 25 mm (1") Kevlar® webbing
- Kevlar® sewing thread
- Protective coating
- Flame resistant (ASTM D 6413-08)
- End loops reinforced with nylon webbing
- 11 intermediate loops
- Overall length : 203 cm (80")
- Minimum break strength : 2 268 kg (5 000 lb)
- Maximum user weight : 227 kg (500 lb)

RDC8011K Fluo orange

RDC8011KR Red

Max. shelf life	Max. service life	Max. combined life (shelf + service)
7 years	5 years	7 years
<i>Important: Products are considered on-condition throughout their shelf & service life and must pass inspections and maintenance recommendations as per the manufacturer's user instructions manual</i>		

Kevlar® is a trademark of E.I. Du Pont de Nemours Co., Inc.