

### UHMWPE and Polyester Fiber Rope

S200 is a double braided rope constructed with a polyester cover and a UHMWPE fiber core.

#### Features

- Specific gravity of 1.20
- Very low elongation
- High strength to weight ratio
- Can be spliced
- Torque free
- Easy to handle

#### Applications

- Pulling lines
- Winch lines
- General working lines
- Heavy lift slings



### SPECIFICATIONS

- Standard color: White  
(Other colours available upon request)

Code	Diameter		kg per 100m	lb per 100'	Average Strength	
	(mm)	(in)			(kg)	(lb)
S2000602	5	3/16	1.4	0.9	891	1 965
S2000802	6	1/4	3.0	2.0	1 529	3 370
S2001002	8	5/16	4.3	2.9	1 826	4 026
S2001202	10	3/8	6.0	4.0	3 900	8 600
S2001402	11	7/16	8.2	5.5	4 800	10 600
S2001602	12	1/2	10.6	7.1	5 400	11 900
S2001802	14	9/16	14.9	10.0	9 980	22 000
S2002002	16	5/8	18.6	12.5	12 246	27 000
S2002402	18	3/4	23.8	16.0	15 880	35 000

**Barry Cordage Ltd.**  
 6110 boul. des Grandes Prairies  
 Montreal QC H1P 1A2 Canada  
 ☎ 514.328.3888 📠 514.328.1963  
 1.800.305.2673 (Canada / USA)

[www.barry.ca](http://www.barry.ca)