

Safeline® rope is constructed with a 50/50 ratio of core to sheath for durability. Solution dyed polyester 16-carrier sheath braided over twisted nylon core strands.

Features

- Semi-static rope
- Easy knotting and handling
- Excellent abrasion resistance
- Sewn terminations available in option

Applications

- Fire rescue
- High angle rescue
- Technical rigging

Certifications

- 3/8" diameter: NFPA 1983/2017 Technical Use
- 7/16" diameter: NFPA 2500(1983) Technical Use, EN 1891, UIAA 107
- 1/2" diameter: NFPA 2500(1983) General Use, ANSI Z359.15, EN 1891, UIAA 107
- 5/8" diameter: NFPA 2500(1983) Technical Use



SPECIFICATIONS

- Standard colors: Red, blue, yellow, orange, green

Diameter		Weight		Break Strength	
(mm)	(in)	(kg/100m)	(lb/100')	(kg)	(lb)
9.5	3/8	7.25	4.87	3 069	6 766
11	7/16	8.72	5.86	3 656	8 061
12.5	1/2	12.22	8.21	4 528	9 983
15.5	5/8	17.89	12.02	6 004	13 237

Elongation

Diameter	@ 300 lbf	@ 600 lbf	@ 1 000 lbf
3/8"	2.8%	5.7%	8.1%
7/16"	2.7%	5.0%	7.7%
1/2"	2.2%	4.2%	6.5%
5/8"	1.6%	2.9%	4.8%

Barry Cordage Ltd.

6110 boul. des Grandes Prairies
 Montreal QC H1P 1A2 Canada
 ☎ 514.328.3888 📠 514.328.1963
 1.800.305.2673 (Canada / USA)

www.barry.ca