

Manufactured by braiding a 16-strand nylon cover over a parallel nylon fiber core. The parallel fibers impart increased strength and durability to this non-spliceable low stretch cord.

### Features

- Lower stretch due to parallel core
- Easy knotting
- Good strength to weight ratio
- Excellent abrasion resistance
- Not spliceable

### Applications

- Utility cord
- Tent / tarpaulin cord
- Flag pole lines
- Lashing



## SPECIFICATIONS

- Standard colors: White, black
- Spool length: 305 m (1000')

Code	Diameter		kg per 100 m	lbs per 100 ft	Average Strength	
	(mm)	(in)			(kg)	(lbs)
SBN02	1.6	1/16	0.21	0.14	122	270
SBN03	2.4	3/32	0.40	0.27	172	380
SBN04	3.2	1/8	0.78	0.52	272	600
SBN05	4	5/32	1.18	0.79	332	733
SBN06	4.8	3/16	1.51	1.01	489	1 080
SBN08	6.4	1/4	2.30	1.54	662	1 460

### Barry Cordage Ltd.

6110 boul. des Grandes Prairies  
 Montreal QC H1P 1A2 Canada  
 ☎ 514.328.3888 📠 514.328.1963  
 1.800.305.2673 (Canada / USA)