

Stable Braid - Polyester Double Braid Rope

A firm polyester double braided rope with high strength, low stretch and excellent resistance to wear.

Features

- Torque-free construction
- Durable
- Excellent abrasion resistance
- High resistance to UV degradation
- Spliceable
- High wear and heat resistance
- Excellent flex-fatigue service life
- Firm flexibility
- Low working elongation

Applications

- Winch Lines
- Secondary mooring lines
- Heavy lift slings
- Material hauling lines
- Pulling and stringing lines



SPECIFICATIONS

- Standard color: White
- Other colors and diameters available upon request

Code	Diameter		kg per 100m	lbs per 100ft	Average strength	
	(mm)	(in)			(kg)	(lbs)
STAB080602	6.4	1/4	3.1	2.1	1 000	2 300
STAB120602	9.5	3/8	6.7	4.5	2 500	5 600
STAB160602	12.7	1/2	12.2	8.2	4 700	10 400
STAB200602	15.9	5/8	20.8	14.0	7 400	16 300
STAB240602	19.1	3/4	26.8	18.0	9 300	20 400
STAB280602	22.2	7/8	40.3	27.1	13 600	29 900
STAB320602	25.4	1	50.6	34.0	17 800	39 200

Elastic elongation at % break strength

10%	20%	30%
1.10% elongation	1.70% elongation	2.70% elongation

Barry Cordage Ltd.

6110 boul. des Grandes Prairies
Montreal QC H1P 1A2 Canada
☎ 514.328.3888 📠 514.328.1963
1.800.305.2673 (Canada / USA)