

Technora® Fiber 12-Strand Rope

The 12-Strand Technora® High Modulus Polyamide (HMPA) fiber rope offers excellent heat resistance and high strength.

Features

- Excellent heat resistance
- Excellent resistance to flex-fatigue
- Extremely strong
- Easily spliceable
- UV resistant urethane coating
- Strength comparable to wire rope
- High strength / low stretch
- Flexible non rotational construction
- Negligible creep/cold flow

Applications

- Technical rigging
- Heliport anti-skid nets
- Wire replacement ropes



SPECIFICATIONS

- Standard colors: Natural tan, black, red

Code	Diameter		kg per 100m	lbs per 100'	Average Strength	
	(mm)	(in)			(kg)	(lbs)
TECH04 COA	3.2	1/8	1.0	0.7	1 542	3 400
TECH06 COA	4.8	3/16	1.9	1.3	2 630	5 800
TECH08 COA	6.4	1/4	2.8	1.9	3 810	8 400
TECH10 COA	7.9	5/16	4.8	3.2	6 032	13 300
TECH12 COA	9.5	3/8	6.4	4.3	8 210	18 100

Barry Cordage Ltd.

6110 boul. des Grandes Prairies
 Montreal QC H1P 1A2 Canada
 ☎ 514.328.3888 📠 514.328.1963
 1.800.305.2673 (Canada / USA)